

5

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

**APPLICATION FOR LETTERS PATENT**

10

15

**METHOD AND SYSTEM FOR PERFORMING  
OPERATIONS AND FOR IMPROVING  
PRODUCTION IN WELLS**

20

25

**INVENTORS**

30

**PHILIP M. SNIDER  
JOSEPH A. ZIEROLF**

35

**ATTORNEY'S DOCKET NO. 200007 USA**

40

05586648.060100

### Cross Reference to Related Applications

This application is a continuation-in-part of patent application serial no. 09/286,650, filed April 6, 1999, entitled "Method And Apparatus For Determining Position In A Pipe".

### Field of the Invention

This invention relates to generally to wells used in the production of fluids such as oil and gas. More specifically, this invention relates to a method and system for performing various operations and for improving production in wells.

### Background of the Invention

Different operations are performed during the drilling and completion of a subterranean well, and also during the production of fluids from subterranean formations via the completed well. For example, different downhole operations are typically performed at some depth within the well, but are controlled at the surface.

A perforating process is one type of downhole operation that is used to perforate a well casing. A conventional perforating process is performed by placing a perforating tool (i.e., perforating gun) in a well casing, along a section of the casing proximate to a geological formation of interest. The perforating tool carries shaped charges that are detonated using a signal transmitted from the surface to the charges. Detonation of the charges creates openings in the casing and concrete around the casing, which are then used to establish fluid communication between the geological formation, and the inside diameter of the casing.

Another example of a downhole operation is the setting of packers within the well casing to isolate a particular section of the well or a particular geological formation. In this case, a packer can be placed within the well casing at a desired depth, and then set by a setting tool actuated from the surface. Other exemplary downhole operations include the placement of logging tools at a particular geological formation or depth within the well casing, and the placement of bridge plugs, casing patches, tubulars, and associated tools in the well casing.

09586648-060100

Sub  
A1  
Ind  
A2  
5

09586648 060100

One critical aspect of any downhole operation involves ascertaining the depth in the well where the operation is to be performed. The depth is typically ascertained using well logs. A conventional well log includes continuous readings from a logging instrument, and an axis which represents the well depths at which the readings were obtained. The instrument readings measure rock characteristics such as natural gamma ray radiation, electrical resistivity, density and acoustic properties. Using these rock characteristics geological formations of interest within the well, such as oil and gas bearing formations, can be identified. The well is initially logged "open hole" which becomes the bench mark for all future logs. After the well is cased, a cased hole log is then prepared and correlated, or "tied in", to the open hole log.

Using the logs and a positioning mechanism, such as a wire line or coiled tubing, coupled to an odometer, a tool can be placed at a desired depth within the well, and then actuated as required to perform the downhole operation. One problem with conventional logging and positioning techniques is that it is difficult to accurately identify the depth of the tool, and to correlate the depth to the open hole logs.

Figure 1 illustrates a prior art perforating process being performed in an oil and gas well 10. The well 10 includes a well bore 12, and a casing 14 within the well bore 12 surrounded by concrete 16. The well 10 extends from an earthen surface 18 through geological formations within the earth, which are represented as Zones A, B and C. The casing 14 is formed by tubular elements, such as pipe or tubing sections, connected to one another by collars 20. In this example the tubular elements that form the casing 14 are about 40 feet long so that the casing collars 20 are forty feet apart. However, tubular elements with shorter lengths (e.g., twenty feet) can be interspersed with the forty feet lengths to aid in depth determinations. Thus in Figure 1 two of the casing collars 20 are only twenty feet apart.

For performing the perforating operation a perforating tool 22 has been lowered into the casing 14 on a wire line 24. A mast 26 and pulleys 28 support the wire line 24, and a wire line unit 30 controls the wire line 24. The wire line unit 30 includes a

09586648-060100

drive mechanism 32 that lowers the wire line 24 and the tool 22 into the well 10, and raises the wire line 24 and the tool 22 out of the well 10 at the completion of the process. The wire line unit 30 also includes an odometer 34 that measures the unwound length of the wire line 24 as it is lowered into the well 10, and equates this measurement to the depth of the tool 22 within the well.

During formation of the well 10 an open hole log 36 was prepared. The open hole log 36 includes various instrument readings, such as gamma ray readings 38 and spontaneous potential (SP) readings 40 which are plotted as a function of depth in feet. For simplicity only a portion of the open hole log 36, from about 7000 feet to about 7220 feet, is illustrated. However, in actual practice the entire well 10 from the surface 18 to the bottom of the well 10 may be logged. The open hole log 36 permits skilled artisans to ascertain the oil and gas containing formations within the well 10 and the most productive intervals of those formations. For example, based on the gamma ray readings 38 and the SP readings 40 it is determined that Zone A may contain oil and gas reserves. It is thus desired to perforate the casing 14 along a section thereof proximate to Zone A.

In addition to the open hole log 36, following casing of the well 10, cased hole gamma ray readings 44 are made, and a casing collar log 42 can be prepared. The casing collar log 42 is also referred to as a PDC log (perforating depth control log). The casing collar log 42 can be used to identify the section of the casing 14 proximate to Zone A where the perforations are to be made.

Using techniques and equipment that are known in the art, the casing collar log 42 can be accurately correlated, or "tied in", to the open hole log 36. However, using conventional positioning mechanisms, such as the wire line unit 30, it may be difficult to accurately place the perforating tool 22 at the required depth within the well. For example, factors such as stretching, elongation from thermal effects, sinusoidal and helical buckling, and deformation of the wire line 24 can affect the odometer readings, and the accuracy of the odometer readings relative to the open hole odometer readings.

Thus, as shown in Figure 1, the odometer readings which indicate the depth of the perforating tool 22, may not equate to the actual depths, as reflected in the open hole log 36 and the casing collar log 42 . In this example, the odometer readings differ from the depths identified in the open hole log 36 and the casing collar log 42 by about 40 feet. With this situation, when the perforating tool 22 is fired, the section of casing 20 proximate to Zone A may be only partially perforated, or not perforated at all.

Because of these tool positioning inaccuracies, various correlative joint logging and wire logging techniques have been developed in the art. For example, one prior art technique uses electronic joint sensors, and electrically conductive wire line, to determine joint-to-joint lengths, and to correlate the odometer readings of the wire line to the casing collar log. Although these correlative joint logging and wire line logging techniques are accurate, they are expensive and time consuming. In particular, additional crews and surface equipment are required, and additional wire line footage charges are incurred.

In addition to tool positioning inaccuracies, computational errors also introduce inaccuracies in depth computations. For example, a tool operator can make computational errors by thinking one number (e.g., 7100), while the true number may be different (e.g., 7010). Also, the tool operator may position the tool by compensating a desired amount in the uphole direction, when in reality the downhole direction should have been used. These computational errors are compounded by fatigue, the weather, and communication problems at the well site.

It would be desirable to obtain accurate depth readings for downhole tools without the necessity for complicated and expensive correlative joint logging and wire logging techniques. In addition, it would be desirable to control down hole operations and processes without having to rely on inaccurate depth readings contaminated by computational errors. The present invention is directed to an improved method and system for performing operations and processes in wells, in which the depths of down hole tools are accurately ascertained and used to control the operations and processes.

Another limitation of conventional downhole operations that are dependent on depth measurements, is that downhole tools must first be positioned in the well, and then actuated from the surface. This requires additional time and effort from well crews. In addition, surface actuation introduces additional equipment and variables to the operations. It would be advantageous to be able to control downhole operations without the requirement of surface actuation of the downhole tools. With the present invention actuation of downhole tools can be performed in the well at the required depth.

### Summary of the Invention

In accordance with the present invention a method and a system for performing various operations in wells, and for improving production in wells, are provided. Exemplary operations that can be performed using the method include perforating processes, packer setting processes, bridge plug setting processes, logging processes, inspection processes, chemical treating processes, casing patch processes, jet cutting processes and cleaning processes. Each of these processes, when performed in a well according to the method, improves the well and improves production from the well.

In an illustrative embodiment the method is used to perform a perforating process in an oil or gas production well. The well includes a well bore, and a well casing, extending from an earthen or subsea surface into various geological zones within the earth. The well casing includes lengths of pipe or tubing joined together by casing collars.

The method includes the initial step of providing identification devices at spaced intervals along the length of the well casing. The identification devices can comprise active or passive radio identification devices installed in each casing collar of the well casing. Each radio identification device is uniquely identified, and its depth, or location, within the well is accurately ascertained by correlation to well logs. Similarly, each casing collar is uniquely identified by the radio identification device contained therein, and a record of the well

including the depth of each casing collar and identification device is established.

The method also includes the step of providing a reader device, and a transport mechanism for moving the reader device through the well casing proximate to the identification devices. In the illustrative embodiment the reader device comprises a radio frequency transmitter and receiver configured to provide transmission signals for reception by the identification devices.

The identification devices are configured to receive the transmission signals, and to transmit response signals back to the reader device. The transport mechanism for the reader device can comprise a wire line, tubulars, coil tubing, a robotic mechanism, a fluid transport mechanism such as a pump or a blower, a free fall arrangement, or a controlled fall arrangement such as a parachute.

In addition to transmitting and receiving signals from the identification devices, the reader device is also configured to transmit control signals for controlling a process tool, as a function of the response signals from the identification devices.

For example, the reader device can control a perforating tool configured to perforate the well casing. Specifically, the reader device and the perforating tool can be transported together through the well casing past the identification devices. In

addition, the reader device can be programmed to transmit the control signal to detonate the perforating tool, upon reception of a response signal from an identification device located at a predetermined depth or location within the well. Stated differently, the reader device can be programmed to control the perforating tool responsive to locating a specific identification device.

As other examples, the reader device can be configured to control setting tools for packers, bridge plugs or casing patches, to control instrument readings from logging tools, and to control jet cutters and similar tools. With the method of the invention the true depth of the process tool can be ascertained in real time by the reader device using response signals from the identification devices. Accordingly, there is no need to ascertain the depth of the tool using an odometer, and expensive wire

09586648.060100

C  
control

logging techniques. In addition, operator computational errors are reduced because true depth readings can be provided without the requirement of additional computations. Further, for some processes, there is no need to transmit signals to the surface, as the reader device can be programmed to control the process in situ within the well.

However, it is to be understood that the method of the invention can also be practiced by transmission of the control signals from the reader device to a controller or computer at the surface, and control of the process tool by the controller or computer. In addition, control of the process tool can be performed dynamically as the process tool moves through the well with the reader device, or statically by stopping the process tool at a required depth. Further, the method of the invention can be used to control a multi stage process, or to control a tool configured to perform multiple processes. For example, a combination packer setting and perforating tool can be configured to perform packer setting and perforating processes, as a function of true depth readings obtained using the method of the invention.

In the illustrative embodiment the system includes the identification devices installed in casing collars at spaced intervals along the well casing. The identification devices include a programmable element, such as a transceiver chip for receiving and storing identification information, such as casing collar and depth designations. Each identification device can be configured as a passive device, an active device having an antenna, or a passive device which can be placed in an active state by transmission of signals through well fluids.

The system also includes the reader device and the process tool configured for transport through the well casing. In addition to the transmitter and receiver, the reader device includes one or more programmable memory devices, such as semiconductor chips configured to receive and store information. The reader device also includes a power source such as a power line to the surface, or a battery. In addition, the reader device includes a telemetry circuit for transmitting the control signals, which can be used to control the process tool, and to provide depth and other



information to operators and equipment at the surface. The system can also include a computer configured to receive and process the control signals, and to provide and store information in visual or other form for well operators and equipment. Further,  
5 the system can include a controller configured to process the control signals for controlling the process tool and various process equipment. The controller can be located at the surface, or on the process tool, to provide a self contained system. Also, the system can be transported to a well site in the form of a kit,  
10 and then assembled at the well site.

#### Brief Description of the Drawings

Figure 1 is a schematic diagram of a prior art downhole operation being performed using well logs and odometer readings from a tool positioning mechanism;  
15

Figure 2 is a flow diagram illustrating steps in the method of the invention for controlling a perforating process in a well;

Figures 3A and 3B are schematic cross sectional views illustrating a system constructed in accordance with the invention for performing the perforating process;  
20

Figure 3C is an enlarged portion of Figure 3B, taken along section line 3C, illustrating a perforating tool of the system;

Figure 3D is an enlarged portion of Figure 3A, taken along section line 3D, illustrating a reader device and an identification device of the system;  
25

Figure 3E is an enlarged cross sectional view taken along section line 3E of Figure 3D illustrating a portion of the reader device;

Figure 3F is a side elevation view of an alternate embodiment active reader device and threaded mounting device;  
30

Figure 4A is an electrical schematic for the system;

Figure 4B is a view of a computer screen for a computer of the system;

Figures 5A and 5B are schematic views illustrating exemplary spacer elements for spacing the reader device of the system from the perforating tool of the system;  
35

Figures 6A-6D are schematic cross sectional views illustrating various alternate embodiment transport mechanisms for the system;

Figures 7A and 7B are schematic cross sectional views illustrating an alternate embodiment system constructed in accordance with the invention for performing a packer setting process in a well;

Figure 7C is an enlarged portion of Figure 7A taken along section line 7C illustrating a threaded connection of a tubing string of the alternate embodiment system; and

Figure 8A-8C are schematic cross sectional views illustrating an alternate embodiment multi stage method and system of the invention for performing a packer setting and a perforating processes in combination.

#### Detailed Description of the Preferred Embodiment

Referring to Figure 2, broad steps in a method for controlling an operation or process in a subterranean well in accordance with the invention are illustrated. The method, broadly stated, includes the steps of:

- A. Providing a process tool.
- B. Providing a reader device in signal communication with the process tool.
- C. Providing a transport mechanism for the process tool and the reader device.
- D. Providing spaced identification devices in a well casing readable by the reader device.
- E. Uniquely identifying each identification device and determining its depth, or location, in the well using well logs.
- F. Programming the reader device to transmit a control signal to the process tool upon reception of a response signal from a selected identification device.
- G. Transporting the process tool and the reader device through the well casing.
- H. Reading the identification devices using the reader device.

I. Transmitting the control signal to the process tool upon reception of the signal from the selected identification device to actuate the process tool at a selected depth.

Referring to Figures 3A-3D, a system 50 constructed in accordance with the invention is illustrated. The system 50 is installed in a subterranean well 52, such as an oil and gas production well. In this embodiment the system 50 is configured to perform a perforating process in the well 52. The perforating process performed in accordance with the invention provides an improved well 52, and improves production from the well 52.

The well 52 includes a well bore 54, and a well casing 56 within the well bore 54 surrounded by concrete 56. The well 52 extends from an earthen surface 60 through geological formations within the earth, which are represented as Zones E, F and G. The earthen surface 60 can be the ground, or alternately a structure, such as an oil platform located above water. In the illustrative embodiment, the well 52 extends generally vertically from the surface 60 through Zones E, F, and G. However, it is to be understood that the method can also be practiced on inclined wells, and on horizontal wells.

A [ The well casing 56 comprises a plurality of tubular elements 62, such as lengths of metal pipe or tubing, connected to one another by collars 64. The casing 56 includes an inside diameter adapted to transmit fluids into, or out of, the well 52, and an outside diameter surrounded by the concrete 58. The collars 64 can comprise couplings having female threads adapted for mating engagement with male threads on the tubular elements 62. Alternately, the collars 64 can comprise weldable couplings adapted for welding to the tubular elements 62.

Also in the illustrative embodiment the casing 56 is illustrated as having the same outside diameter and inside diameter throughout its length. However, it is to be understood that the casing 56 can vary in size at different depths in the well 52, as would occur by assembling tubulars with different diameters. For example, the casing 56 can comprise a telescoping structure in which the size thereof decreases with increasing depth.



00586648-060100

5 In the illustrative embodiment, the identification devices 72 comprise passive radio identification devices (PRIDs). PRIDs are commercially available and are widely used in applications such as to identify merchandise in retail stores, and books in libraries. The PRIDs include a circuit which is configured to resonate upon reception of radio frequency energy from a radio transmission of appropriate frequency and strength. Passive PRIDs do not require a power source, as the energy received from the transmission signal provides the power for the PRIDs to transmit a reply signal during reception of the transmission signal.

15 The identification device 72 includes an integrated circuit chip, such as a transceiver chip, having memory storage capabilities. The integrated circuit chip can be configured to receive RF signals and to encode and store data based on the signals. During a data encoding operation each identification device 72 can be uniquely identified such that each collar 64 is also uniquely identified. This identification information is indicated by the C1-C8 designations in Figures 3A and 3B. In addition, the depth of each collar 64 can be ascertained using well logs, as previously explained and shown in Figure 1. The depth information can then be correlated to the identification information encoded into the identification device 72. A record can thus be established identifying each collar 64 and its true depth in the well 52.

25 Alternately, as shown in Figure 3F, identification device 72A can be in the form of an active device having a separate power source such as a battery. In addition, the identification device 72A can include an antenna 89 for transmitting signals. Alternately, an identification device (not shown) can be configured to transmit signals through a well fluid or other transmission medium within the well 52. Such an identification device is further described in previously cited parent application serial no. 09/286,650, which is incorporated herein by reference.

35 As also shown in Figure 3F, the identification device 72A can be contained in a threaded mounting device 87. The threaded mounting device 87 can comprise a rigid, non-conductive material such as a plastic. The threaded mounting device 87 is configured

0958648-050100

to be screwed into the middle portions of the casing collar 64 (Figure 3D), and to be retained between adjacent tubular elements of the casing 56. The threaded mounting device 87 includes a circumferential groove 91 for the antenna 89, and a recess 93 for the identification device 72A. If desired, the antenna 89 and the identification device 72A can be retained in the groove 91 and the recess 93 using an adhesive or a suitable fastener.

Referring to Figure 3E, the reader device 70 is shown in greater detail. The reader device 70 is configured to transmit RF transmission signals at a selected frequency to the identification devices 72, and to receive RF response signals from the identification devices 72. As such, the reader device 70 includes a base member 77 having a transmitter 73 configured to transmit transmission signals of a first frequency to the identification devices 72. The reader device 70 includes a receiver 71 on the base member 77 configured to receive signals of a second frequency from the identification devices 72.

Preferably, the transmitter 73 is configured to provide relatively weak transmission signals such that only an identification device 72 within a close proximity (e.g., one foot) of the reader device 70 receives the transmission signals. Alternately, the antenna of the reader device 70 can be configured to provide highly directional transmission signals such that the transmission signals radiate essentially horizontally from the reader device 70. Accordingly, the transmission signals from the reader device 70 are only received by a single identification device 72 as the reader devices passes in close proximity to the single identification device 72.

In addition to the transmitter 73 and the receiver 71, the reader device 70 includes a cover 79 made of an electrically non-conductive material, such as plastic or fiberglass. The reader device 70 also includes o-rings 75 on the base member 77 for sealing the cover 79, and a cap member 81 attached to the base member 77 which secures the cover 79 on the base member 77. In addition, the reader device 70 includes spacer elements 83 formed of an electrically non-conductive material such as ferrite, ceramic or plastic, which separate the transmitter 73 and the receiver 71 from the base member 77. In the illustrative

embodiment, the base member 77 is generally cylindrical in shape, and the spacer elements 83 comprise donuts with a half moon or contoured cross section.

Referring to Figure 4A, an electrical schematic for the system 50 is illustrated. As illustrated schematically, each identification device 72 includes a memory device 110, in the form of a programmable integrated circuit chip, such as a transceiver chip, configured to receive and store identification information. As previously explained, the identification information can uniquely identify each casing collar 64 with an alpha numerical, numerical or other designator. In addition, using previously prepared well logs, the depth of each uniquely identified casing collar 64 can be ascertained.

As also shown in Figure 4A, the reader device 70 includes the transmitter 73 for transmitting transmission signals to the identification devices 72, and the receiver 71 for receiving the response signals from the identification devices 72. The reader device 70 can be powered by a suitable power source, such as a battery, or a power supply at the surface. In addition, the reader device 70 includes a memory device 112, such as one or more integrated circuit chips, configured to receive and store programming information. The reader device 70 also includes a telemetry circuit 114 configured to transmit control signals in digital or other form, through software 116 to a controller 118, or alternately to a computer 122.

As is apparent the software 116 can be included in the controller 118, or in the computer 122. In addition, the computer 122 can comprise a portable device such as a lap top which can be pre-programmed and transported to the well site. Also, as will be further explained, the computer 122 can include a visual display for displaying information received from the reader device 70. The controller 118, or the computer 122, interface with tool control circuitry 120, which is configured to control the perforating tool 68 as required.

In the illustrative embodiment, the tool control circuitry 120 is in signal communication with the detonator 74 (Figure 3C) of the perforating tool 68. The tool control circuitry 120 can be located on the perforating tool 68, on the reader device 70, or at









the perforating tool 68 and the reader device 70 in the casing 56. Again, the parachute can operate in a well fluid, or in air contained in the casing 56.

Referring to Figures 7A-7C, an alternate embodiment system 50A constructed in accordance with the invention is illustrated. The system 50A is installed in a subterranean well 52A, such as an oil and gas production well. In this embodiment the system 50A is configured to perform a packer setting process in the well 52A.

The well 52A includes a well bore 54A, and a well casing 56A within the well bore 54A surrounded by concrete 58A. The well casing 56A comprises a plurality of tubular elements 62A, such as lengths of metal pipe or tubing, connected to one another by collars 64A. The well 52A extends from an earthen surface 60A through geological formations within the earth, which are represented as Zones H and I.

For performing the packer setting process, the system 50A includes a packer setting tool 68A, an inflation device 98A for the packer setting tool 68A, and a reader device 70A in signal communication with the packer setting tool 68A. In this embodiment, the inflation device 98A is located on the surface 60A such that a wire, or other signal transmission medium must be provided between the packer setting tool 68A and the inflation device 98A. The packer setting tool 68A can include an inflatable packer element designed for inflation by the inflation device 98A and configured to sealingly engage the inside diameter of the casing 56A. In Figure 7B, the inflatable packer element of the packer setting tool 68A has been inflated to seal the inside diameter of the casing 56A proximate to Zone I.

The system 50A also includes a plurality of identification devices 72 (Figure 3D) attached to the collars 64A on the casing 56A, and readable by the reader device 70A. In addition, the system 50A includes a transport mechanism 66A for transporting the packer setting tool 68A and the reader device 70A through the well casing 56A to Zone I. In this embodiment, the transport mechanism 66A comprises a tubing string formed by tubular elements 102A. As shown in Figure 7C, each tubular element 102A includes a male tool joint 94A on one end, and a female tool

09586648 060100

joint 96A on an opposing end. This permits the tubular elements 102A to be attached to one another to form the transport mechanism 66A. In addition, the packer setting tool 68A can include a central mandrel in fluid communication with the inside  
5 diameter of the transport mechanism 66A.

The reader device 70A is programmed to transmit a control signal to the inflation device 98A upon actuation by a selected identification device 72 (Figure 3D). For example, in the packer setting process illustrated in Figures 7A and 7B, coupling C4A is  
10 located proximate to the upper level, or entry point into Zone I. Since it is desired to inflate the inflatable packer element of the packer setting tool 68A while it is proximate to Zone I, the reader device 70A can be programmed to transmit the control signal to the inflation device 68A when it reaches coupling C4A. In this  
15 embodiment a spacer element 88A separates the packer setting tool 68A and the reader device 70A. In addition, the packer setting tool 68A is located downhole relative to the reader device 70A.

In order to insure that the packer setting sequence is  
20 initiated at the right time additional factors must be considered as previously explained. These factors can include the velocity (V) of the packer setting tool 68A and the reader device 70A, and the time required to inflate the inflatable packer element of the packer setting tool 68A. Alternately, the packer setting tool 68A  
25 can be stopped at a particular coupling (e.g., coupling C5A) and then inflated as required. In this case the reader device 70A can be programmed to transmit the control signals to the visual display 124 (Figure 4B) on the surface 60A when the packer tool 68A passes a coupling 64A at the required depth. The operator  
30 can then control the inflation device 98A to initiate inflation of the packer setting tool 68A. Alternately the inflation sequence can be initiated automatically by the tool control circuit 120 (Figure 4A).

In each of the described processes the method of the  
35 invention provides an improved well. For example, in the perforating process of Figures 3A and 3B, the well 52 can be perforated in the selected zone, or in a selected interval of the selected zone. Production from the well 52 is thus optimized and

the well 52 is able to produce more fluids, particularly oil and gas.

Referring to Figures 8A-8C, a multi stage operation performed in accordance with the method of the invention is illustrated. Initially, as shown in Figure 8A, a combination tool 130 is provided. The combination tool 134 includes a packer setting tool 132 and a perforating tool 134, which function substantially as previously described for the packer setting tool 68A (Figure 7B), and the perforating tool 68 (Figure 3A) previously described. In addition, the combination tool 134 includes the reader device 70 and the casing 56 includes identification devices 72 (Figure 3D) substantially as previously described. As also shown in Figure 8A, the combination tool 130 is transported through the casing 56 using the gravity transport mechanism 66G. Alternately, any of the other previously described transport mechanisms can be employed.

Next, as shown in Figure 8B, the packer setting tool 132 is actuated such that an inflatable packer element of the tool 132 seals the casing 56 at a desired depth. In this embodiment the packer setting tool 132 is a self contained unit, with an integral inflation source. As with the previously described embodiments, the reader device 70 provides control signals for controlling the packer setting tool 132, and the packer setting process. For example, the inflatable packer element of the packer setting tool 132 can be inflated when the reader device 70 passes a selected coupling 64, and receives a response signal from the identification device 72 contained within the selected coupling 64. As also shown in Figure 8B, the perforating tool 134 separates from the packer setting tool 132 and continues to free fall through the casing 56.

Next, as shown in Figure 8C, the perforating tool 132 is controlled such that detonation and explosive sequences are initiated substantially as previously described. Again the reader device 70 provides control signals, for controlling the perforating tool 132 to initiate the detonation and explosive sequences at the proper depth. As indicated by the dashed arrows in Figure 8C explosion of the charge assemblies 80 (Figure 3C) of the

perforating tool 134 forms openings in the casing 58 and the concrete 58.

Thus the invention provides a method and a system for performing various operations or processes in wells and for improving production from the wells. While the invention has been described with reference to certain preferred embodiments, as will be apparent to those skilled in the art, certain changes and modifications can be made without departing from the scope of the invention as defined by the following claims.

090404 : 000000